WHAT IS CLAIMED IS:

1. A packet communications apparatus to be used in a network system wherein user terminals that can be linked via a network to said apparatus send/receive packets to/from a server for authentication and a file server connected via a network to said apparatus, comprising:

a plurality of network interfaces;

a learned address table containing information for identifying one of said network interfaces through which to send a packet;

a packet forwarding unit that selects a port through which to forward a packet by referring to said learned address table, according to the state of said network interfaces, and forwards or discards a packet sent from the user terminal, addressed to the server for authentication/file server and vice versa;

a processor for directive packets to change state that receives a directive packet to change state, the packet holding a directive to change the state of a specific network interface to one of the connected state, disconnected state and stateless, via said packet forwarding unit from the server for authentication; and

state managers, each installed in each network interface and each that receives a directive packet to

change state from said processor for directive packets to change state and changes the state of the network interface to one of the connected state, disconnected state and stateless, according to the directive packet to change state.

    2. The packet communications apparatus according to claim 1, wherein:

    said network system further includes a server for address assignment that dynamically leases an address to a user terminal linked to it via a network or networks and a router;

    said apparatus further includes a filtering table in which the source address of a packet it received is registered;

    said processor for directive packets to change state, upon receiving a directive packet to change state that directs it to register a specific address registered in said filtering table into said learned address table, registers the specific address into the learned address table; and

    said apparatus unconditionally forwards a packet whose destination address is registered in the learned address table and forwards a packet whose destination address is registered in said filtering table, but not registered in the learned address table, provided the source

address of the packet is the router or the server for
authentication.

    3. The packet communications apparatus according
to claim 1, wherein:

    each of said network interfaces further includes a
link down detector that finds whether a network link
terminated to the interface is now workable;

    each of said state managers, when said line down
detector detect a link-down, changes the state of the
network interface in which the link-down has now been
detected to the disconnected state;

    each of said state managers, when a user terminal
is user-authenticated by said server for authentication,
changes the state of the network interface to which the user
terminal is linked to the connected state; and

    said packet forwarding unit, upon receiving a
packet through a network interface set in the disconnected
state, does not forward the packet to a network interface
set in the disconnected or connected state, but forwards the
packet to only a specific network interface, and upon
receiving a packet through a network interface set in the
connected state, does not forward the packet to a network
interface set in the disconnected state.

    4. A packet communications apparatus to be used in
a network system wherein user terminals that can be linked

via a network to said apparatus send/receive packets to/from
a server for authentication and a file server connected via
a network to said apparatus, comprising:

physical interfaces, each making the connection to
a network;

a packet forwarding unit that selects a port through
which to forward a packet;

filtering units that perform packet filtering, each
located between each of said physical interfaces and the
packet forwarding unit and comprising a filtering table
containing information for forwarding or discarding a
packet and a packet processor that discards a packet or
transfers a packet to said packet forwarding unit, according
to the contents of said filtering table; and

a processor for directives to change filtering that
transfers a directive to change filtering from said server
for authentication to the appropriate one of said filtering
units, changes the information in the filtering table
initially set to discard all received packets, according to
the directive from said server for authentication, and
sequentially adds information for forwarding such packets
to said file server that include the address of a user
terminal that has now been user-authenticated by said server
for authentication as the source address to said filtering
table.

5. A packet communications apparatus to be used in a network system wherein user terminals that can be linked via a network to said apparatus send/receive packets to/from a server for authentication and a file server connected via a network to said apparatus, comprising:

network interfaces for sending/receiving packets to/from the user terminals, the server for authentication and the file server;

an IP address registration table in which the addresses of the user terminals user-authenticated by the server for authentication are registered; and

a packet forwarding unit that forwards a packet whose source address matches an address registered in said IP address registration table and encapsulates a packet whose source address is not registered in the IP address registration table and then sends the encapsulated packet to a specific address.